



DE-106

### FEATURES :

- Pocket Size
- Self-Storing Test Leads
- O.V. Protection (Fuse, Diode, MOV)
- Suitable For Hobby And DIY Use

### TEMP. / HUMIDITY:

- Operation: 0°C~40°C (32°F~104°F) Below 80% R.H. (no condensation)
- Storage: -10°C~50°C (14°F~122°F) Below 70% R.H. (no condensation)

### DIMENSION & WEIGHT:

- 105(L)x65(W)x24(H)mm (4.14"x2.56"x0.95")
- Approx. 89g (0.19lbs) (Excluding Battery)

### ACCESSORIES:

- Battery 1.5V(AAA).....1
- Instruction Manual.....1
- Test Lead (Black & Red Attached with Meter)..... 1

### MEASUREMENT RANGE:

(23°C ± 5°C, 80% R.H. MAX.)

Measurement	Ranges	Accuracy
$\frac{V}{\text{---}}$ (DCV)	0 – 10 – 50 – 250 – 500V(2KΩ/V)	Within ± 4% F.S.
$\frac{V}{\sim}$ (ACV)	50 – 250 – 500V(2Ω/V)	Within ± 5% F.S.
<b>Battery test</b>	1.5V (AAA, AA, C, D, and Button Cell) and 9V	Within ± 10% END Of BAD and GOOD
$\frac{A}{\text{---}}$ (DCA)	25 – 250mA	Within ± 4% F.S.
$\Omega$ (Resistance)	x1K (0 – 500KΩ ,Center 5KΩ )	Within ± 5% Of arc
<b>dB</b> (Decibels)	+4dB to +56dB on AC Voltage range	Within ± 5% F.S.