

Digital Thermometer (K-Type)

DE-3003 / DE-3004



DE-3003

DE-3004

FEATURES :

- DE-3003 :Single Channel
DE-3004 :Two Channels
- Data Hold Function
- Resolution :
DE-3003 : 0.1°C / 0.1°F, 1°C / 1°F
DE-3004 : 1°C / 1°F
- Wide Measuring Range : -50°C~1300°C (-58°F~1999°F)
- Low Battery Indication
- Celsius (°C) or Fahrenheit (°F) For Selection
- Offset Adjustment
- "OL" Display When Overload or No Signal Input

SPECIFICATIONS:

- Input Protection :60V DC or 24Vrms AC Maximum
- By:9V, NEDA 1604, IEC 6F22, JIS 006P

TEMP. / HUMIDITY:

- Operation:0°C~50°C (32°F~122°F) Below 80% R.H.
(no condensation)
- Storage:-10°C~60°C (14°F~140°F) Below 70% R.H.
(no condensation)

DIMENSION & WEIGHT:

- 148(L) x 71(W) x 36(H)mm
(5.83"x2.8"x42")
- Approx. 210g(0.46 lbs.)
(Including Battery)

MEASUREMENT RANGES:

DE-3003

Measurement Range	Accuracy
-50 °C~1000 °C	±(0.3%rdg+1°C)
1000 °C~1300 °C	±(0.5%rdg+1°C)
-58 °F~1999 °F	±(0.3%rdg+2°F)

DE-3004

Measurement Range	Accuracy
0 °C~1000 °C	±(0.3%rdg+1°C)
1000 °C~1300 °C	±(0.5%rdg+1°C)
32 °F~1999 °F	±(0.3%rdg+2°F)
-50 °C~0 °C	±2 °C
-58 °F~32 °F	±4 °F

ACCESSORIES:

- Battery 9V.....1
- Instruction Manual.....1
- Thermocouple (NR-39)
DE-3003.....1
DE-3004.....2
- Rubber Holster + Stand Rack..... 1